


shopvalves.com

DIMENSIONS & DAT	TA CERTIFIED FOR:	
Representative:	Order:	
Customer:	Order:	
Project:		
Requirements:		
	By: Date:	



DIMENSIONS ARE IN INCHES [MM]





LIST OF MATERIALS:		
NAME OF PART	MATERIAL	
BODY	ASTM-A479,TYPE 304	
CAP	ASTM-A351,GR CF8	
VALVE	AICI-440C	
SEAT	303 STN.STL.	
SCREEN	304 STN.STL.	
GASKET SEAT	STAINLESS STEEL	
BIMETALIC DISC	RGR NICKEL PLATED	
GASKET	304 STN.STL NON-ASBESTOS	
NUTS	304 STN.STL	
RIVET	STAINLESS STEEL	
LABEL	304 STN.STL	

DESIGN INF	FORMATION	
MAXIMUM ALLOWABLE PRESSURE (VESSEL DESIGN)	400 psig[28 bar] at 649°F[343°C]	
MAXIMUM OPERATING PRESSURE	319 psig [22 bar]	
WEIGHT:	2.7331bs [1.24 kg]	



Armstrong International, Inc. Belgium Division Herstal, Hauts Sart

Armstrong (0032) 240.90.90 Fax() 240.40.33 Posted on Armstrong's homepage www.armstronginternational.com

Product	CD No.	Date
AB3000 WHITH INTEGRATED FLANGE W/OUT CONNECTOR	2226	27/01/09
III SST SSTWESTOR	Rev; A	By; A.MORTADA