



SH-2000 Bimetallic Steam Traps

All Stainless Steel

For pressures to 28 bar...Cold Water Capacities to 2175 kg/hr

Description

SH Series Superheat Steam Traps operate by the effect that rising temperature has on the thermostatic bimetallic elements.

The effect of rising temperature on bimetallic elements operates the Armstrong SH-2000 bimetallic steam trap. It adjusts to changing conditions because the curving of the bimetallic elements, caused by increasing temperature, compensates for increasing pressure.

At start-up, the valve is wide open, which allows a large volume of non-condensables and cold condensate to be removed from the system. When the system reaches steam temperature, the elements become sufficiently hot to pull on the trap's valve stem, closing the valve.

The valve remains closed until the bimetallic elements cool, thus allowing the valve to crack open, venting the condensate and non-condensables, and then close again when steam temperature is reached.

The Armstrong SH-2000 has a sealed, stainless steel body that is lightweight, compact and highly resistant to corrosion. It is adaptable to an Armstrong 360° Universal Connector or a Trap Valve Station (TVS). This makes it easy to install and replace, as the trap can be removed while the connector remains in-line. That means savings in labor cost and ultimate flexibility—because inverted bucket, thermostatic, thermostatic wafer, disc, and float and thermostatic steam traps can all be installed on the same connector.

Maximum Operating Conditions

Maximum allowable pressure (vessel design):
28 bar @ 427°C

Maximum operating pressure: 400 psi (28 bar)

Materials

Body:	Stainless Steel
Valve & Seat Elements:	Titanium, Ni-Cr and Stainless Steel
Ring:	Stainless Steel
Cap Assembly:	Stainless Steel
Flange:	ASTM A105 Zinc plated
Retainer Ring:	Carbon Steel
Spiral Wound Gasket:	Stainless Steel
Label:	Aluminum




Table ST-186-1. SH-2000 Cold Water Capacity

